

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 11/9/2021 Revision date: 3/9/2026 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : HH-66 Vinyl Cement

1.2. Other means of identification

Synonyms : PVC Vinyl Adhesive

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
Restrictions on use : No additional information available

1.4. Supplier's details

Supplier

RH Adhesives
308 Old High Street
Acton, MA, 01720
USA
T 1-978-897-8000
sales@rhadhesives.com

1.5. Emergency phone number

Emergency number : 1-800-535-5053 INFOTRAC; 1-352-323-3500 INFOTRAC International

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Serious eye damage/eye irritation, Category 2A	H319	Causes serious eye irritation.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Precautionary statements (GHS US)

H373 - May cause damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, lighting equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe vapors, mist, spray.
P264 - Wash hands, forearms, and other exposed area thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTER, a doctor if you feel unwell.
P314 - Get medical advice or attention if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P370+P378 - In case of fire: Use dry chemical powder, alcohol resistant foam, carbon dioxide (CO₂) to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of § 1910.1200

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Name	Product identifier	%	GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR § 1910.1200)
Methyl ethyl ketone	CAS-No.: 78-93-3	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Acetone	CAS-No.: 67-64-1	15 - 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	CAS-No.: 108-88-3	5 - 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Get medical attention if symptoms occur.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. nausea, vomiting.
Symptoms/effects after skin contact	: Absorbed through the skin. Repeated exposure may cause skin dryness or cracking. Redness. Itching.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Alcohol-resistant foam. Carbon dioxide.
------------------------------	--

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Heating will cause a rise in pressure with a risk of bursting. In case of fire and/or explosion do not breathe fumes.

Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Evacuate the danger area. Eliminate all ignition sources if safe to do so.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Wear fire/flammable resistant/retardant clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : Ventilate spillage area. Do not touch or walk on the spilled product. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors, mist. Evacuate unnecessary personnel. No action shall be taken without appropriate training or involving any personal risk.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Evacuate unnecessary personnel. Avoid breathing vapours, mist. Use non-sparking tools.

Environmental precautions : Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Remove ignition sources.

Methods for cleaning up : Caution : this product can cause the floor to be slippery. Move containers from spill area. Prevent entry to sewers and public waters. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). Clean contaminated surfaces with an excess of water. Use non-sparking tools.

Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Precautions for safe handling	: Provide adequate ventilation to minimize dust and/or vapor concentrations. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapors, mist. Eliminate all ignition sources if safe to do so. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Take precautionary measures against static discharge. Use explosion-proof equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Store in a well-ventilated place. Store in a dry place. Keep cool. Keep away from food, drink and animal feed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in accordance with local, regional, national or international regulation.
Storage area	: Store in dry, cool, well-ventilated area.
Incompatible products	: Strong acids. Strong bases. Oxidizing agent. Amines. Inorganic acids. Metallic salts.
Incompatible materials	: Direct sunlight. Sources of ignition.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Methyl ethyl ketone (78-93-3)	
USA - ACGIH® - Threshold Limit Values	
Local name	Methyl ethyl ketone (MEK)
ACGIH® TLV® TWA	75 ppm
ACGIH® TLV® STEL	150 ppm
Remark (ACGIH®)	TLV® Basis: URT irr; Embryo/fetal dam; Headache; Dizziness. Notations: Skin; BEI
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	Methyl ethyl ketone
BEI (BLV)	2 mg/l Parameter: Methyl ethyl ketone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butanone (Methyl ethyl ketone)
OSHA PEL TWA	590 mg/m ³ 200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Methyl ethyl ketone; MEK; 2-butanone; ethyl methyl ketone
Cal/OSHA PEL (OEL TWA)	590 mg/m ³ 200 ppm
Cal/OSHA STEL	885 mg/m ³ 300 ppm

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl ethyl ketone (78-93-3)	
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	2-Butanone (Methyl ethyl ketone(MEK))
NIOSH REL 10h TWA	200 ppm
NIOSH REL (STEL)	300 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Acetone (67-64-1)	
USA - ACGIH® - Threshold Limit Values	
Local name	Acetone
ACGIH® TLV® TWA	594 mg/m ³
	250 ppm
ACGIH® TLV® STEL	1187 mg/m ³
	500 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH® - Biological Exposure Indices	
Local name	Acetone
BEI (BLV)	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift - Notations: Ns
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL TWA	2400 mg/m ³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Acetone [Dimethyl ketone]
Cal/OSHA PEL (OEL TWA)	1200 mg/m ³
	500 ppm
Cal/OSHA STEL	1780 mg/m ³
	750 ppm
Cal/OSHA C	3000 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Acetone
NIOSH REL 10h TWA	250 ppm

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acetone (67-64-1)	
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Toluene (108-88-3)	
USA - ACGIH® - Threshold Limit Values	
Local name	Toluene
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: CNS, Hearing & Visual impair; Female repro system eff; Pregnancy loss. Notations: OTO (Ototoxicant); A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2025
USA - ACGIH® - Biological Exposure Indices	
Local name	Toluene
BEI (BLV)	0.3 mg/g Kreatinin Parameter: o-Cresol - Medium: urine - Sampling time: End of shift - Notations: B 0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: Prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: End of shift
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL TWA	200 ppm
OSHA PEL (Ceiling)	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Toluene; toluol
Cal/OSHA PEL (OEL TWA)	37 mg/m ³
	10 ppm
Cal/OSHA STEL	560 mg/m ³
	150 ppm
Cal/OSHA C	500 ppm
Remark (Cal/OSHA)	S - Skin notation and Protecting Clothing
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Toluene
NIOSH REL 10h TWA	100 ppm
NIOSH REL (STEL)	150 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-2 (NIOSH Pocket Guide to Chemical Hazards (NPG))
Monitoring methods	
Monitoring methods	Refer to all applicable national, international and local regulations or provisions.

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation. Handle in accordance with good industrial hygiene and safety procedures. Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:

Chemical resistant gloves (according to NIOSH standard). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Selection of protective gloves should be made based on the type of task performed.

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided

Respiratory protection:

Where excessive vapor, mist, or dust may result, use approved respiratory protection equipment. All respirators must conform to specifications for efficiency and performance indicated by OSHA Standard 29 CFR 1910.134 and NIOSH Standards

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: White
Odor	: strong aromatic odor/sharp mint like fragrance
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 35 °C (> 95 °F)
Flash point	: -14 °C (7 °F, ASTM D-56)
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: > 1 (heavier than air)
Relative density	: 0.83 (water=1)
Density	: 827.2 g/l
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 1232 – 1408 mm ² /s (40 °C, 104 °F)
Explosion limits	: Lower explosion limit: 1 Vol-% Upper explosion limit: 12 Vol-%
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	: 53 % (446 g/l)
-------------	------------------

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor. Can form explosive mixtures with air. Heating may cause a fire or explosion.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization: Will not occur. Reacts vigorously with strong oxidizers and acids.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating. Extremely high or low temperatures. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases. Amines. Inorganic acids. Metallic salts.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2054 mg/kg
LD50 dermal rat	> 10 ml/kg
LD50 dermal rabbit	5000 mg/kg
LC50 Inhalation - Rat [ppm]	11700 ppm/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	15688 mg/kg
LC50 Inhalation - Rat	44 g/m ³
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	15688 mg/kg body weight
ATE US (vapors)	44 mg/l/4h
ATE US (dust, mist)	44 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Toluene (108-88-3)	
LC50 Inhalation - Rat	25.7 mg/l/4h
ATE US (oral)	2600 mg/kg body weight
ATE US (dermal)	12000 mg/kg body weight
ATE US (vapors)	25.7 mg/l/4h
ATE US (dust, mist)	25.7 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified

HH-66 Vinyl Cement	
Viscosity, kinematic	1232 – 1408 mm ² /s (40 °C, 104 °F)

Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. nausea, vomiting.
Symptoms/effects after skin contact	: Absorbed through the skin. Repeated exposure may cause skin dryness or cracking. Redness. Itching.
Symptoms/effects after eye contact	: Causes serious eye irritation. Redness. Lacrimation. Itching. Blurred vision.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

SECTION 12 Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Methyl ethyl ketone (78-93-3)	
LC50 - Fish [1]	3130 – 3320 mg/l (96 h; Pimephales promelas [flow-through])
EC50 - Crustacea [1]	520 mg/l (48 h; Daphnia magna)
EC50 - Crustacea [2]	5091 (48 h; Daphnia magna)
NOEC chronic algae	93 mg/l

Acetone (67-64-1)	
LC50 - Fish [1]	4144.846 mg/l (96 h, Oncorhynchus mykiss)
EC50 - Crustacea [1]	1679.66 mg/l (48 h, Daphnia magna, static)

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Acetone (67-64-1)	
LC50 - Fish [2]	6210 – 8120 mg/l (96 h, Pimephales promelas, static)
EC50 - Crustacea [2]	12600 – 12700 mg/l (48 h, Daphnia magna)
Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (96 h; Pimephales promelas [flow-through])
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (48 h; Daphnia magna [static])
LC50 - Fish [2]	12.6 mg/l (96 h; Pimephales promelas [static])
EC50 - Crustacea [2]	11.5 mg/l (48 h; Daphnia magna)
EC50 72h - Algae [1]	> 433 mg/l (Pseudokirchneriella subcapitata)
EC50 72h - Algae [2]	12.5 mg/l (Pseudokirchneriella subcapitata)
NOEC chronic fish	1.4 mg/l (Oncorhynchus kisutch)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)

12.2. Persistence and degradability

HH-66 Vinyl Cement	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

HH-66 Vinyl Cement	
Bioaccumulative potential	No data available concerning bioaccumulation.

Methyl ethyl ketone (78-93-3)	
Partition coefficient n-octanol/water (Log Pow)	0.29

Acetone (67-64-1)	
BCF - Fish [1]	0.69
Partition coefficient n-octanol/water (Log Pow)	-0.24

Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.7

12.4. Mobility in soil

HH-66 Vinyl Cement	
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Ozone	: Not classified
Other adverse effects	: No other effects known.
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)





Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not dispose of the packaging without first carrying out the necessary cleaning. Do not pierce or burn, even after use.

Additional information : Flammable vapors may accumulate in the container.

Ecological waste information : Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1133	UN1133	1133	1133
14.2. Proper Shipping Name			
Adhesives	ADHESIVES	ADHESIVES	Adhesives
14.3. Transport hazard class(es)			
3	3	3	3
			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
No supplementary information available			

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN1133

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
 B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
 IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
 T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
 TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
 TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

UN-No. (TDG) : UN1133
Explosive Limit and Limited Quantity Index : 5 L
Excepted quantities (TDG) : E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 5 L
Emergency Response Guide (ERG) Number : 128

IMDG

Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E2
Packing instructions (IMDG) : P001
Packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC02
Tank instructions (IMDG) : T4
Tank special provisions (IMDG) : TP1, TP8
EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG) : B
Properties and observations (IMDG) : Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

IATA

Special provision (IATA) : A3
PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
ERG code (IATA) : 3L

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	5 - 10%
---------	------------------	---------

Methyl ethyl ketone (78-93-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Methyl ethyl ketone (78-93-3)	
CERCLA RQ	5000 lb

Acetone (67-64-1)	
CERCLA RQ	5000 lb

Toluene (108-88-3)	
Listed on EPA Hazardous Air Pollutant (HAPS) Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits	
CERCLA RQ	1000 lb

15.2. International regulations

CANADA

Methyl ethyl ketone (78-93-3)	
Listed on the Canadian DSL (Domestic Substances List)	

Acetone (67-64-1)	
Listed on the Canadian DSL (Domestic Substances List)	

Toluene (108-88-3)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

No additional information available

National regulations

Methyl ethyl ketone (78-93-3)	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	

Acetone (67-64-1)	
Listed on INSQ (Mexican National Inventory of Chemical Substances)	

Toluene (108-88-3)	
Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on EPA HAPs Chronic Dose Response Assessment List - Carcinogens Listed on EPA HAPs Acute Dose Response Assessment List – Exposure limits	

15.3. State regulations

WARNING:

This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SCAQMD Rule 1168 – Adhesive and Sealant Applications:

This product is an adhesive as defined under SCAQMD Rule 1168. The regulatory VOC content is 446 g/L, determined using SCAQMD Method 316A. Users in the South Coast Air Quality Management District should verify applicability of local VOC limits and exemptions for their specific use and container size.

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Revision date	: 3/9/2026
Issue date	: 11/9/2021
Data sources	: Supplier's safety documents. ECHA (European Chemicals Agency).
Training advice	: Training staff on good practice.
Other information	: SDS prepared by. H2 Compliance.

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms	
ACGIH	American Conference of Governmental Industrial Hygienists
AIHA	American International Health Alliance
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAS-No.	Chemical Abstracts Service number
DOT	Department of Transport
DSL	Canada DSL (Domestic Substances List)
EC50	Median effective concentration
EC-No.	European Community number
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
N.O.S.	Not Otherwise Specified

HH-66 Vinyl Cement

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Abbreviations and acronyms	
NDSL	Canada NDSL (Non-Domestic Substances List)
NIOSH	National Institute for Occupational Safety and Health
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
OSHA	Occupational Safety Health Administration
PPE	Personal protection equipment
SDS	Safety Data Sheet

Indication of changes:
Sections 1-16.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.